STEEL EQUIPMENT CORPORATION

PO BOX 307, 897 ROUTE 910, INDIANOLA, PA 15051 USA
PHONE: 412.767.9290 FAX: 412.767.9272
www.steelequip.com e-mail: steelequip@pgh.net



DC Main Mill Drive Motors for Sale

HP: 4000
Power: 700VDC
Speed: 225/675 RPM
Mfr: GE
Previous Use: Tandem Cold Mill Drive Motors
Design: 2000/2000HP Double Armature, 10 pole, Class H Insulation
Quantity: 3 motors available [2 were in service and operating when removed, 1 is rebuilt spare]

Motors have been disassembled and are in storage.
Contact Dev Lemster for pricing.

over for outline drawing>>>>>>>


GENERAL ELECTRIC
58D147224
OUTLINE 8000HP DOUBLE ARM
ADL-58X170627
NAME | TYPE | POLES | CAP/CT | VOLT
(2) MOTOR | MCF | 10 | 4000HP | 700
GE 176m# 102A
w/o " " 969A
DSC " " 3104 & 3105
MILL STAND MOTOR
OVERALL 430.20
35.50 72.50 31.75 67.75 85.50 77.50 31.75 67.75 85.50 73.70
BRG #1 16.6X11.6 W/O THRUST .100 TOTAL END PLAY
BRG #2 15.0X15.0 (INSULATED)
BRG #3 15.0X15.0 (INSULATED)
(2) GROUNDING BRUSHES
SPEED LIMIT SWITCH SEE NOTE #5
.75D PIPE TAP OIL INLET FAR SIDE EA. PED.
BRG. TEMP RELA THIS SIDE ALL PEDS. SEE NOTE #9
(2) KEYS 90° APART 3.25 X 2.50 KEYWAYS 1.25 DEEP IN SHAFT
2.5D PIPE TAP OIL OUTLET FAR SIDE EA. PED.
OIL DRAIN
DRILL & REAM FOR 1.50 DOWELS, (4) HOLES 1.50 +.002 -.000 DIA. PEDEST. #1, 2, 3, 5, AT ASSEMBLY
OIL GAUGE THIS SIDE EA. PED.
DRILL & REAM FOR .75 D DOWELS, (2) HOLES .750 +.002 -.000 DIA. EA. STATOR AT ASSEMBLY
"B" SCREENED AIR IN
AIR OUT
COUPLING & BELT GUARD
SHAFT
EC-46 TACH
PULSE TACH
GROUND PAD SEE NOTE #10
50-13 TAPS
LIMIT LINES SEE NOTE #1
SEE NOTE #11
LIMIT LINES SEE NOTE #1
ROTATION
END DOORS
WINDOW
119.00
58.56
107.00
24.06
14.00
47.50 MIN.
57.06 TO
SEE NOTE-4
COMM. FIELD RESISTOR
RECEIVED
54 RS
AUG 10 1982
PROCESS DIVISION
3
119.00 OVERALL
27.30 131.70 29.70 153.30 30.70
24.05
39.75
19.75
14.50
SHAFT
2.375 DIA. HOLE FOR 2.00 DIA. FOUNDATION BOLT, (12) HOLES. SEE NOTE #6
1.75 DIA. HOLE FOR 1.50 DIA. END BOLT, (16) HOLES SEE NOTE #6
TACH DRIVE MOUNT
28.70
46.88
59.50
27.70
56.06
12.62
5.50
5.88 16.03 5.88 5.88 16.03 5.88
17.30 48.67 32.06 59.97 20.70 50.27 32.06 59.97 20.70
352.70
409.70 OVERALL
APPROXIMATE WEIGHTS
(2) ROTOR WITH SHAFT & BLK. CPLG (41,862 LBS EA) 83,724 LBS.
(2) STATOR WITH BR. RIGS. & SHIELDS (44,000 LBS EA) 88,000
BASE 20981
STUB SHAFT 5458
16.6X11.6 BRG. & PED. 3118
(2) 15.0X15.0 BRG. & PED. (3828 LBS. EA.) 6656
TACH DRIVE & SP. LIMIT SWITCH 200.88
TOTAL 208,137 LBS.
7299-D1-80022
310 G-4F-0003
ITEM # 1
SHEET # 1
DATE: JUL 20 1982
4 MAGNETIC BEARING PIN JAW & OUTLETS ADDED NOTE #9 & DOWELS
SCHEMECTADY
58D147224
HALF PLAN OF BASE BEARING ON FOUNDATION AT "A-A" (SEE NOTE 3)